




VANTAGE

PBH02 CHECKMATE VANTAGE TWO POINT HARNESS

TECHNICAL DATA SHEET - ISSUE 1

Our entry level fall arrest safety harness with one rear 'dorsal' and one front 'sternum' attachment point.

Lightweight, easy to don with four points of adjustment to ensure a better fit. Available with carbon steel fittings, this harness is suitable for fall arrest and work restraint as well as work positioning on inclined surfaces via a rope and grab.



Attachment Points

The front and rear "D" rings are safe to connect to any EN compliant fall protection system.




Reinforced Webbing

Potential stress points are reinforced for an extra level of safety and durability.



Label Pouch

All individual harness information is kept securely inside the label pouch for easy reference and protection.



Horizontal comfort legs

With Horizontal legs it eliminates pinch points around the groin, and also allows much more free movement.

SCOPE OF USE

The PBH02 is designed to support the body and distribute the forces to prevent serious injury and keep the worker in a safe position ready for rescue in the event of a fall.

Certified fall arrest points are clearly marked with an A, the rear "D" should always be your primary anchorage, although front "D" connection is permitted but is primarily for work positioning.

For fall arrest the PBH02 must only be used in conjunction with an energy absorber or load limiting device with a maximum impact force of 6kN.

When used for fall arrest a predetermined rescue plan must be a part of your safe system of work.

Recommended minimum anchor strength - 12kN.



Contrast Stitching

Contrast stitching is used for easy inspection, prior to donning.



Fall Arrest Indicator

Fall arrest indicating tabs allow the user to easily and confidently determine if the harness has been subjected to fall forces.



PBH02

CHECKMATE VANTAGE TWO POINT HARNESS

TECHNICAL DATA SHEET - ISSUE 1

Prod. Code	Description	Weight
PBH02-S	Standard 2 Point Harness (Pass Through Buckles) Small	1.1kg
PBH02-ML	Standard 2 Point Harness (Pass Through Buckles) Medium/large	1.1kg
PBH02-XL	Standard 2 Point Harness (Pass Through Buckles)	1.1kg
PBH02-Q-S	Standard 2 Point Harness (Quick Connect Buckles)	1.2kg
PBH02-Q-ML	Standard 2 Point Harness (Quick Connect Buckles)	1.2kg
PBH02-Q-XL	Standard 2 Point Harness (Quick Connect Buckles)	1.2kg
PBH02-#-++		
# Denotes quick connect -Q		
+ Denotes Size S-M/L-XL		
PBH02-Q-S = 2 Point standard harness with quick connect and in the size small.		



■ Attachment Points

Rear D fall arrest attachment point (Dorsal) Front
D fall arrest attachment point (Sternum)

■ Fittings

Carbon steel, zinc plated

■ User Weight

140Kg Maximum

■ Webbing

45mm Polyester

■ Comfort Legs

Horizontal legs that do not ride up in to groin

■ Stand Up Rear D

To allow easy connection

■ 4 Points Of Adjustment

Maximum adjustment across all sizes

Standards

- EN 361:2002