



VANTAGE


PBH02-E CHECKMATE VANTAGE TWO POINT

ELASTICATED HARNESS

TECHNICAL DATA SHEET - ISSUE 1

Our elasticated fall arrest safety harness with one rear 'dorsal' and one front 'sternum' attachment point.

Lightweight, easy to don with four points of adjustment and a top half made from elasticated webbing to ensure a more comfortable fit. Available with carbon steel fittings, this harness is suitable for fall arrest and work restraint as well as work positioning on inclined surfaces via a rope and grab.



Attachment Points

The front and rear "D" rings are safe to connect to any EN compliant fall protection system.



Reinforced Webbing

Potential stress points are reinforced for an extra level of safety and durability.



Label Pouch

All individual harness information is kept securely inside the label pouch for easy reference and protection.



Elasticated Webbing

The top half of the harness is made from elasticated webbing allowing for some extra stretch and comfort whilst being active.

SCOPE OF USE

The PBH02-E is designed to support the body and distribute the forces to prevent serious injury and keep the worker in a safe position ready for rescue in the event of a fall.

Certified fall arrest points are clearly marked with an A, the rear "D" should always be your primary anchorage, although front "D" connection is permitted but is primarily for work positioning.

For fall arrest the PBH02-E must only be used in conjunction with an energy absorber or load limiting device with a maximum impact force of 6kN.


When used for fall arrest a predetermined rescue plan must be a part of your safe system of work.

Recommended minimum anchor strength - 12kN.



Parking Keepers

Keepers on the chest allow you to stow the spare lanyard leg safely and will break in the event of a fall.



Contrast Stitching

Contrast stitching is used for easy inspection, prior to donning.



PBH02-E

CHECKMATE VANTAGE TWO POINT ELASTICATED HARNESS

TECHNICAL DATA SHEET - ISSUE 1

Prod. Code	Description	Weight
PBH02-E-S	Elasticated 2 Point Harness (Pass Through Buckles) Small	1.1kg
PBH02-E-ML	Elasticated 2 Point Harness (Pass Through Buckles) Medium/large	1.1kg
PBH02-E-XL	Elasticated 2 Point Harness (Pass Through Buckles)	1.1kg
PBH02-EQ-S	Elasticated 2 Point Harness (Quick Connect Buckles)	1.2kg
PBH02-EQ-ML	Elasticated 2 Point Harness (Quick Connect Buckles)	1.2kg
PBH02-EQ-XL	Elasticated 2 Point Harness (Quick Connect Buckles)	1.2kg
PBH02-##-++		
## Denotes Elastic webbing - E and Quick connect -Q		
+ Denotes Size S-M/L-XL		
PBH02-EQ-S = 2 Point Elasticated harness with quick connect and in the size small.		



■ Attachment Points

Rear D fall arrest attachment point (Dorsal) Front
D fall arrest attachment point (Sternum)

■ Fittings

Carbon steel, zinc plated

■ User Weight

140Kg Maximum

■ Webbing

45mm Polyester

■ Elasticated Webbing

For a better fit and maximum comfort

■ Parking keeper

To stow your spare lanyard leg

■ Stand Up Rear D

To allow easy connection

■ 4 Points Of Adjustment

Maximum adjustment across all sizes

Standards

- EN 361:2002