

TECHNICAL DATA SHEET

LOADFAST STRAPS

TDS137



Loadfast Straps Technical Data Sheet

The information on this data sheet is for marketing purposes only and Checkmate reserves the right to amend at any time without notice. The information must not be relied on for use, which must be obtained from the product marking and user information.



principal features

- ▶ Widths: 25mm, 35mm, 50mm & 75mm
- ▶ Breaking Loads: 1t, 2t, 5t & 10t
- ▶ Various lengths and end fittings
- ▶ Labelled with relevant information for traceability and safety
- ▶ Wear sleeves available to protect from sharp objects and abrasive loads
- ▶ Will not damage the surface of the goods being lashed
- ▶ Unaffected by grease, oil, dirt or sea water
- ▶ High strength to weight ratio
- ▶ Easily examined
- ▶ End fittings:
 - CH= Claw Hook
 - DR= D Ring
 - FSH= Flat Snap Hook
 - TS= Twisted Snap Hook
 - ET= E Tract

principal materials

- ▶ Zinc plated carbon steel
- ▶ High tenacity low stretch polyester

standards

- ▶ EN 12195:2000

ordering information

Part No.	Description
▶ RAT#T*M+	Ratchet of various lengths and end fittings
▶ RAT-W/S	Ratchet wear sleeves

= Tonnage e.g. 5T = 5 tonnes

* = Length e.g. 5M = 5 metres

+ = End fittings e.g. CH = Claw Hook

e.g. RAT6T15MCH = 6 tonne 15 metre ratchet with claw hook(s)



CHECKUSOUT

www.checkmatesafety.co.uk

