

TECHNICAL DATA SHEET

DUPLEX WEBSLINGS

TDS139



Duplex Webslings Technical Data Sheet

Checkmate Duplex Webslings

Checkmate duplex webslings are available in a range of lengths and tonnage colour coded accordingly for easy identification.



product features

- SWL: 1,000kg up to 12,000kg- colour coded
- Widths: 30mm up to 300mm
- Factor of safety: 7:1
- Eyes: Becket, flat, reversed, twisted or a range of compatible hardware
- High strength to weight ratio
- Absorbs shock loads
- Light and flexible makes them easy to handle
- Wear sleeves available to protect from abrasion and sharp objects in either webbing or polyurethane
- Helps prevent damage to the surface of goods being lifted
- Unaffected by grease or oil
- Certificates of conformity are supplied with goods
- Easily examined

principal materials

- Polyester

standards

- EN1492-1:2000

ordering information

Part No.	Description	Weight
DS#*+	Various lengths and tonnage web slings	N/A

= Length e.g. 5 = 5 metres

* = Tonnage e.g. 5 = 5 tonnes

+ = eyes or hardware e.g. Becket



CHECKUSOUT

www.checkmatesafety.co.uk



The information on this data sheet is for marketing purposes only and Checkmate reserves the right to amend at any time without notice. The information must not be relied on for use, which must be obtained from the product marking and user information.

TDS139 ISSUE 04