

TECHNICAL DATA SHEET

ANCHOR STROP

TDS75



Anchor Straps AST-ASTR-ASTW Technical Data Sheet

ANCHOR STROPS: AST/ASTR/ASTW

Available in 25mm polyester webbing, polyester roundsling and 6mm galvanised steel wire. They are used for quick and simple anchorage to a large variety of structures.



product features

- ▶ Polyester or steel
- ▶ All complete with wear sleeves
- ▶ Lightweight
- ▶ Simple to use
- ▶ Versatile
- ▶ Range of lengths available
- ▶ Compatible end anchor for HLL1 systems

principal materials

- ▶ **ASTR**
Roundsling, polyester yarn, polyester outer cover
- ▶ **ASTW**
Galvanised steel cable and eyes, alloy ferrule, protective plastic cover.
- ▶ **AST**
25mm polyester webbing endless sling. Polyester wear sleeve

standards

- ▶ EN795 Class B

ordering information

Part No.	Description	Weight
▶ AST	Polyester webbing sling with wear sleeve	0.1kg (+0.1kg)pm
▶ ASTR	Black polyester roundsling	0.84kg [4m circ]
▶ ASTW	Galvanised wire with protective cover	0.5kg [1m]

When ordering a webbing or roundsling anchor strop please note our measurements refer to the circumference and not EWL



CHECKUSOUT

www.checkmatesafety.co.uk



The information on this data sheet is for marketing purposes only and Checkmate reserves the right to amend at any time without notice. The information must not be relied on for use, which must be obtained from the product marking and user information.

TDS75 ISSUE 04