

TECHNICAL DATA SHEET

HLL2W & HLL4W

TDS 114



HLL2W & HLL4W Technical Data Sheet

Checkmate Webbing Ratchet Temporary Horizontal Life Line

HLL2W is a temporary life line designed to be used for restraint or fall arrest applications. Spanning up to 20m the system can accommodate 2 users at a maximum combined weight of 200kg.

HLL4W is a temporary life line designed to be used for restraint or fall arrest applications. Spanning up to 20m the system can accommodate 4 users at a maximum combined weight of 400kg.



Product Features

- Lightweight 25mm Polyester Webbing
- Clear heat seal labels for protection
- Contrast colour stitching for easy inspection
- Max length 20m
- Max number of users is 2 for the HLL2W and 4 for the HLL4W
- HLL2W up to a maximum combined weight of 200kg
- HLL4W up to a maximum combined weight of 400kg
- 15kN minimum anchorage strength

Standards

EN795-2012 TYPE B & C
TS 16415:2013

Ordering information

Part No.	Description	No. of Users
HLL2W	Temporary Webbing Type Horizontal lifeline, minimum working length: 3.0m, maximum working length: 20.0m, Max 2 users	2
HLL4W	Temporary Webbing Type Horizontal lifeline, minimum working length: 3.0m, maximum working length: 20.0m, Max 4 users	4



CHECKUSOUT

www.checkmatesafety.co.uk



TDS 114 ISSUE 06