

TECHNICAL DATA SHEET

VANTAGE PBH05

TDS 08



VANTAGE-PBH05 Technical Data Sheet

Checkmate Vantage 05 Riggers Harness .
The Vantage-PBH05 harness is Checkmate's premium Rope Access harness designed for suspended work tasks.

VANTAGE™

Safety by Design



Attachment Points

Upper connectivity via dorsal and sternum with ventral and lateral connectivity at the waist.



Rapid Don Buckles

Optional click lock buckles for quick and simple donning and removal of harness.



Vented WB & Leg Loops

Breathable padding for comfort and support reducing Hotspots and Sweat patches.



Storable Side D

Fold D rings back on themselves to keep out of the way when not in use



Neck Protector

Leather patch sewn onto the inside edge of the shoulder yoke for added comfort.



Parking Keepers

Breakaway keepers for lanyard storage



TDS 08 ISSUE 10

www.checkmatesafety.co.uk

The information on this data sheet is for marketing purposes only and Checkmate reserves the right to amend at any time without notice. The information must not be relied on for use, which must be obtained from the product marking and user information

TECHNICAL DATA SHEET

VANTAGE PBH05

TDS 08



Scope of use

The Vantage-PBH05 is designed to support the body and distribute the forces to prevent serious injury and keep the worker in a safe position ready for rescue in the event of a fall. Certified fall arrest points are clearly marked with an A, the rear "D" should always be your primary anchorage, although front "D" connection is permitted for fall arrest but is primarily for work positioning. Side "D" are for work positioning only. The front suspension "D" is to be used for suspended work and when used as a Sit harness. For fall arrest the Vantage-PBH05 must only be used in conjunction with an energy absorber or load limiting device with a maximum impact force 6kN. When used for fall arrest a pre-determined rescue plan must be a part of your safe system of work. Recommended minimum anchor strength - 12kN.

Principal materials

- Polyester Webbing, nylon, Steel and Aluminium

Standards

- EN 361, EN 358, EN 813

User Weight

- 140kg Maximum [Including tools and equipment]



Ordering information

Part No.	Description	Weight
PBH05 **	Full Body harness with dorsal & sternal D-ring, work positioning side D-rings, frontal suspension work D-ring, shoulder pad, waist pad & leg pads	2400g

* = Size XS, S/M, L/XL, 2XL/3XL, Universal
E.g. PBH05 XS = PBH05 Extra small



www.checkmatesafety.co.uk